

MI 3100 s EurotestEASI

NEW
Multifunctional electrical
installation tester

**Basic
electrical
installation
safety tester**



MI 3100 s EurotestEASI is a fast, accurate and easy to use multifunctional measuring instrument which performs a basic set of installation safety tests according to IEC/EN 61557. Besides, the MI 3100 s EurotestEASI enables on-line voltage monitoring, phase sequence testing and earth resistance measurement. EurotestEASI is equipped with integrated characteristics of fuses and RCDs for PASS / FAIL evaluation of test results.

Measuring functions:

- Insulation resistance with DC voltage from 50 V to 1000 V;
- Continuity of PE conductors with 200 mA test current with polarity change;
- Continuity of PE conductors with 7 mA test current without RCD tripping;
- Line impedance;
- Loop impedance;
- Loop impedance with Trip Lock RCD function;
- TRMS voltage and frequency;
- Phase sequence;
- RCD testing (general and selective, type AC, A, F);
- Earth resistance (3-wire method).

Key features:

- Built-in help screens for referencing on site.
- Built-in fuse tables for automatic evaluation of the line / loop impedance result.
- Monitoring of all 3 voltages in real-time.
- Automatic polarity reversal on continuity test.
- Loop impedance test without tripping the RCD.
- Built-in charger and rechargeable batteries as standard accessory.
- Automated RCD testing procedure.

APPLICATION

- Initial and periodic testing of domestic and industrial installations.
- Testing of single and multiphase systems.
- Testing of TT and TN supply systems.

STANDARDS

- Functionality:
EN 61557
- Other reference standards for testing:
IEC/EN 60364-4-41;
EN 61008;
EN 61009;
BS 7671;
AS/NZ 3017;
- Electromagnetic compatibility (EMC):
EN 61326
- Safety (LVD):
EN 61010-1;
EN 61010-031
EN 31010-2-030
EN 31010-2-032

Technical specification

Function		Measuring range	Resolution	Accuracy
CONTINUITY	Test Current 7 mA 2-wire	0.00 Ω ... 19.99 Ω 20.0 Ω ... 1999 Ω	0.1 Ω 1 Ω	$\pm(5\% \text{ of } r. + 5 \text{ digits})$
	Test Current 200 mA 2-wire	0.00 Ω ... 19.99 Ω 20.0 Ω ... 199.9 Ω 200.0 Ω ... 1999 Ω	0.01 Ω 0.1 Ω 1 Ω	$\pm(3\% \text{ of } r. + 3 \text{ digits})$ $\pm(5\% \text{ of } r.)$ $\pm(5\% \text{ of } r.)$
INSULATION RESISTANCE	Test Voltage 50/100/250 V	0.00 M Ω ... 19.99 M Ω 20.0 M Ω ... 99.9 M Ω 100.0 M Ω ... 199.9 M Ω	0.01 M Ω 0.1 M Ω	$\pm(5\% \text{ of } r. + 3 \text{ digits})$ $\pm(10\% \text{ of } r.)$ $\pm(20\% \text{ of } r.)$
	Test Voltage 500/1000 V	0.00 M Ω ... 19.99 M Ω 20.0 M Ω ... 199.9 M Ω 200 M Ω ... 999 M Ω	0.01 M Ω 0.1 M Ω 1 M Ω	$\pm(5\% \text{ of } r. + 3 \text{ digits})$ $\pm(5\% \text{ of } r.)$ $\pm(10\% \text{ of } r.)$
RCD	RCD Uc	0.00 V ... 19.99 V 20.0 V ... 99.9 V	0.1 V	$(-0\%/+15\%) \text{ of } r. \pm 10 \text{ digits}$ $(-0\%/+15\%) \text{ of } r.$
	RCD (t),	0.0 ms ... 40.0 ms 0.0 ms ... max.time	0.1 ms	$\pm 1 \text{ ms}$ $\pm 3 \text{ ms}$
	RCD I Ramp	0.2xI Δ N ... 1.1xI Δ N (AC) 0.2xI Δ N ... 1.5xI Δ N (A), I Δ N $\geq 30 \text{ mA}$ 0.2xI Δ N ... 2.2xI Δ N (A), I Δ N < 30 mA	0.05xI Δ N	$\pm 0.1xI\Delta N$
IMPEDANCE	Zline L-L, L-N Ipsc	0.00 Ω ... 9.99 Ω 10.0 Ω ... 99.9 Ω 100 Ω ... 999 Ω 1.00 k Ω ... 9.99 k Ω	0.01 Ω 0.1 Ω 1 Ω 10 Ω	$\pm(5\% \text{ of } r. + 5 \text{ digits})$ $\pm(10\% \text{ of } r.)$
	Zloop L-PE, Ipfc	0.00 Ω ... 9.99 Ω 10.0 Ω ... 99.9 Ω 100 Ω ... 999 Ω 1.00 k Ω ... 9.99 k Ω	0.01 Ω 0.1 Ω 1 Ω 10 Ω	$\pm(5\% \text{ of } r. + 5 \text{ digits})$ $\pm(10\% \text{ of } r.)$
VOLTAGE	TRMS	0 ... 550 V	1 V	$\pm(2\% \text{ of } r. + 2 \text{ digits})$
	Frequency	0.00 Hz ... 9.99 Hz 10.0 Hz ... 499.9 Hz	0.01 Hz 0.1 Hz	$\pm(0.2\% \text{ of } r. + 1 \text{ digits})$
EARTH RESISTANCE	3 wire	0.00 Ω ... 19.99 Ω 20.0 Ω ... 199.9 Ω 200.0 Ω ... 9999 Ω	0.01 Ω 0.1 Ω 1 Ω	$\pm(5\% \text{ of } r. + 5 \text{ digits})$
GENERAL	Power supply	9 VDC (6x1.5 V battery or accu, size AA)		
	Overvoltage category	1000 V DC CAT II; 600 V CAT III; 300 V CAT IV		
	Protection class	double insulation		
	Weight	1.3 kg		
	Size (l x h x w)	230 x 103 x 115 mm		

Ordering information

Standard set

MI 3100 s



- Instrument EurotestEASI
- Schuko-plug test cable, 1.5 m
- Test lead, 3 x 1.5 m
- Test probe, 3 pcs (blue, black, green)
- Crocodile clip, 3 pcs (blue, black, green)
- Power supply adapter + 6 NiMH rechargeable batteries, size AA
- Soft carrying neck belt
- Soft carrying bag
- Short instruction manual
- Instruction manual on CD
- Handbook on CD
- Calibration certificate

Optional accessories

Photo	Order No.	Description
	A 1110	Three phase adapter
	A 1111	Three phase adapter with switch
	A 1201	Insulated rod for CONTINUITY measurement
	A 1202	Additional extension part for A 1201
	A 1164	Test lead, black, 50 m
	A 1153	Test lead, black, 20 m
	A 1154	Test lead, black, 4 m
	A 1198	Magnetic contact probe
	A 1160	Fast charger for 8 AA batteries with a set of 6 NiMH bat., type AA
	S 2026	Earth test set, 3-wire, 20 m
	S 2027	Earth test set, 3-wire, 50 m

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery. Subject to technical change without notice.



Measuring and Regulation Equipment Manufacturer
 METREL d.d.
 Ljubljanska 77
 SI-1354 Horjul
 Tel: + 386 (0)1 75 58 200
 Fax: + 386 (0)1 75 49 226
 E-mail: metrel@metrel.si
 http://www.metrel.si



2-A, Bizsol House, Plot No. 22,
 Second Floor, Near Vascon ITPark,
 Indiranagar Wadala Road,
 Nashik - 422006, Maharashtra, INDIA
 Ph.no. 9960999900, 9371236688
 Email : sales@nsmtechnologies.co.in
 www.nsmtechnologies.co.in